



POWER MAX DRILL - MEDIUM / HIGH SPEED MACHINING

- Suitable for high speed cutting due to newly developed raw-material and new coating.
- 适于干式切削, 高速切削, 最新开发的原材料和涂层.

PF505 ...series



EDP. No.	Dia.	F.L	OAL	SH.Dia.	STOCK	EDP. No.	Dia.	F.L	OAL	SH.Dia.	STOCK
PF505030	3.0	25	60	3	•	PF505067	6.7	47	87	7	•
PF505031	3.1	27		4	•	PF505068	6.8				•
PF505032	3.2				•	PF505069	6.9				•
PF505033	3.3	30	65	4	•	PF505070	7.0	52	92	8	•
PF505034	3.4				•	PF505071	7.1				•
PF505035	3.5				•	PF505072	7.2				•
PF505036	3.6				•	PF505073	7.3				•
PF505037	3.7				•	PF505074	7.4				•
PF505038	3.8	33	71	5	•	PF505075	7.5	56	96	9	•
PF505039	3.9				•	PF505076	7.6				•
PF505040	4.0				•	PF505077	7.7				•
PF505041	4.1	33	71	5	•	PF505078	7.8	62	105	10	•
PF505042	4.2				•	PF505079	7.9				•
PF505043	4.3	36	71	5	•	PF505080	8.0	68	115	11	•
PF505044	4.4				•	PF505081	8.1				•
PF505045	4.5				•	PF505082	8.2				•
PF505046	4.6				•	PF505083	8.3				•
PF505047	4.7				•	PF505084	8.4				•
PF505048	4.8	39	71	5	•	PF505085	8.5	62	105	10	•
PF505049	4.9				•	PF505086	8.6				•
PF505050	5.0				•	PF505087	8.7				•
PF505051	5.1	39	83	6	•	PF505088	8.8	68	115	11	•
PF505052	5.2				•	PF505089	8.9				•
PF505053	5.3				•	PF505090	9.0				•
PF505054	5.4	43	83	6	•	PF505091	9.1	68	115	11	•
PF505055	5.5				•	PF505092	9.2				•
PF505056	5.6				•	PF505093	9.3				•
PF505057	5.7				•	PF505094	9.4				•
PF505058	5.8				•	PF505095	9.5				•
PF505059	5.9	47	87	7	•	PF505096	9.6	68	115	11	•
PF505060	6.0				•	PF505097	9.7				•
PF505061	6.1				•	PF505098	9.8				•
PF505062	6.2	47	87	7	•	PF505099	9.9	68	115	11	•
PF505063	6.3				•	PF505100	10.0				•
PF505064	6.4				•	PF505101	10.1				•
PF505065	6.5				•	PF505102	10.2				•
PF505066	6.6				•	PF505103	10.3				•

Data P272

EDP. No.	Dia.	F.L.	OAL	SH.Dia.	STOCK	EDP. No.	Dia.	F.L.	OAL	SH.Dia.	STOCK
PF505104	10.4				•	PF505141	14.1				•
PF505105	10.5				•	PF505142	14.2				•
PF505106	10.6				•	PF505143	14.3				•
PF505107	10.7	68	115	11	•	PF505144	14.4				•
PF505108	10.8				•	PF505145	14.5	83	143	15	•
PF505109	10.9				•	PF505146	14.6				•
PF505110	11.0				•	PF505147	14.7				•
PF505111	11.1				•	PF505148	14.8				•
PF505112	11.2				•	PF505149	14.9				•
PF505113	11.3				•	PF505150	15.0				•
PF505114	11.4				•	PF505151	15.1				•
PF505115	11.5	71	121	12	•	PF505152	15.2				•
PF505116	11.6				•	PF505154	15.4				•
PF505117	11.7				•	PF505155	15.5	90	152	16	•
PF505118	11.8				•	PF505156	15.6				•
PF505119	11.9				•	PF505157	15.7				•
PF505120	12.0				•	PF505158	15.8				•
PF505121	12.1				•	PF505160	16.0				•
PF505122	12.2				•	PF505161	16.1				•
PF505123	12.3				•	PF505163	16.3	95	155	17	•
PF505124	12.4				•	PF505165	16.5				•
PF505125	12.5	75	125	13	•	PF505170	17.0				•
PF505126	12.6				•	PF505171	17.1				•
PF505127	12.7				•	PF505172	17.2				•
PF505128	12.8				•	PF505175	17.5	100	157	18	•
PF505129	12.9				•	PF505177	17.7				•
PF505130	13.0				•	PF505178	17.8				•
PF505131	13.1				•	PF505180	18.0				•
PF505132	13.2				•	PF505181	18.1				•
PF505133	13.3				•	PF505182	18.2	105	160	19	•
PF505134	13.4				•	PF505185	18.5				•
PF505135	13.5	80	134	14	•	PF505190	19.0				•
PF505136	13.6				•	PF505191	19.1				•
PF505137	13.7				•	PF505195	19.5	110	163	20	•
PF505138	13.8				•	PF505197	19.7				•
PF505139	13.9				•	PF505200	20.0				•
PF505140	14.0				•						

Data ⓘ P272

μm = 1/1000mm

Tolerance	Dia.	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30
Cutting Edge (h8)		0	0	0	0	0
		-14	-18	-22	-27	-33
Shank (h6)		0	0	0	0	0
		-6	-8	-9	-11	-13